



Hollow Taper Shanks for Automatic Tool Changing acc. to ISO 12164/DIN 69 893 Part 1 and 2 - with Gripper Groove

Rev. 12-1101 Page 1 of 1  
Uncontrolled Document



- For use with machining centers, milling machines, special-purpose machines with automatic tool changing.
- Central, axial coolant supply via coolant tube.
- Torque transmission via 2 driving grooves at taper end.
- 2 flange grooves for the tool magazine.
- Position notch.
- Bore for identification chip DIN 69 873 in the flange.



## HSK-A25 to 63 Tool Holder Blanks (619.525)

TAC Rockford stocks HSK-A32, HSK-A40, HSK-A50, HSK-A63, HSK-A80, HSK-A100, and HSK-A125 in a variety of diameters and lengths. HSK-A160 blanks are available on request as well.

Taper	Gauge Length	Diameter	Part Number
HSK-A25	100	25	<a href="#">619.525.025.100</a>
HSK-A32	120	40	<a href="#">619.532.040.120</a>
HSK-A40	100	40	<a href="#">619.540.040.100</a>
HSK-A50	100	50	<a href="#">619.550.050.100</a>
HSK-A50	200	50	<a href="#">619.550.050.200</a>
HSK-A50	160	63	<a href="#">619.550.063.160</a>
HSK-A50	200	63	<a href="#">619.550.063.200</a>
HSK-A50	175	80	<a href="#">619.550.080.175</a>
HSK-A 63	100	63	<a href="#">619.563.063.100</a>
HSK-A/T 63	140	63	<a href="#">619.563.063.140</a>
HSK-A63	200	63	<a href="#">619.563.063.200</a>
HSK-A63	160	80	<a href="#">619.563.080.160</a>
HSK-A63	180	80	<a href="#">619.563.080.180</a>
HSK-A63	250	80	<a href="#">619.563.080.250</a>
HSK-A63	250	100	<a href="#">619.563.100.250</a>
HSK-A/T 63	140	108	<a href="#">619.563.108.140</a>