



Hollow Taper Shanks for Manual Tool Changing acc. to ISO 12164/DIN 69 893
 Part 1 and 2 - without Gripper Groove

Rev. 12-1101 Page 1 of 1
 Uncontrolled Document



- Preferably for use with spindles in transfer lines and special-purpose machines without automatic tool changing, stub spindles, extensions or reducers.
- Central, axial coolant supply.
- Torque transmission via 2 driving grooves at taper end.

HSK-C63 to 100 Tool Holder Blanks (639.563)



Taper	Gauge Length	Diameter	Part Number
HSK-C63	100	63	639.563.063.100
HSK-C63	200	63	639.563.063.200
HSK-C63	160	80	639.563.080.160
HSK-C63	200	80	639.563.080.200
HSK-C63	175	100	639.563.100.175
HSK-C80	100	80	639.580.080.100
HSK-C80	134	80	639.580.080.134
HSK-C80	200	80	639.580.080.200
HSK-C80	200	127	639.580.127.200
HSK-C100	100	100	639.590.100.100
HSK-C100	200	100	639.590.100.200
HSK-C100	225	125	639.590.125.225
HSK-C100	200	127	639.590.127.200

TAC Rockford Product Line

Machine Tool Gauges, Tool Changer Alignment, Runout Test Arbors, Workholding Systems, Tool Holders, Adapters and Extensions, Tool Holder Blanks, Machine Tool Accessories, Coolant Tubes and Gauges, Heat Shrink Systems, Rapid Prototyping


Tool Holders



Gauges



Accessories



Rapid Prototyping

