



Hollow Taper Shanks for High-Speed Cutting (HSC) acc. to the Pre-Standard DIN 69 893 Part 5 and 6 - with Gripper Groove

Rev. 12-1101 Page 1 of 1
Uncontrolled Document



- For use with high-frequency spindles and wood working machines.
- Rotationally symmetrical, without driving grooves.
- Torque transmission via friction grip.
- Central coolant supply via coolant tube is possible.



HSK-E Tool Holder Blanks (659.500)

TAC Rockford stocks HSK-E32, HSK-E40, HSK-E50, and HSK-E63 blanks in a variety of diameters and lengths. Other sizes are available - contact us with your requirements.

Taper	Gauge Length	Diameter	Part Number
HSK-E25	100	25	659.525.025.100
HSK-E25	100	45	659.525.045.100
HSK-E32	100	32	659.532.032.100
HSK-E40	100	40	659.540.040.100
HSK-E50	100	50	659.550.050.100
HSK-E63	100	63	659.563.063.100

TAC Rockford Product Line

Machine Tool Gauges, Tool Changer Alignment, Runout Test Arbors, Workholding Systems, Tool Holders, Adapters and Extensions, Tool Holder Blanks, Machine Tool Accessories, Coolant Tubes and Gauges, Heat Shrink Systems, Rapid Prototyping


Tool Holders



Gauges



Accessories



Rapid Prototyping

