

· Maximum circular deviation between outer taper and D1 \leq 0.006 mm.

Taper (D)	Length (L)	h6 (D1)	L1	L2	D2	Part Number
HSK-A 32	55	16	17	27	32	681.00114020130
HSK-A 32	55	22	19	31	40	681.00114020140
HSK-A 32	65	27	21	33	48	681.00114020150
HSK-A 40	50	16	17	27	32	681.00114020230
HSK-A 40	55	22	19	31	40	681.00114020240
HSK-A 40	65	27	21	33	48	681.00114020250
HSK-A 50	50	16	17	27	32	681.00114020330
HSK-A 50	55	22	19	31	40	681.00114020340
HSK-A 50	65	27	21	33	48	681.00114020350
HSK-A 50	65	32	24	38	58	681.00114020360
HSK-A 63	60	16	17	27	32	681.00114020430
HSK-A 63	60	22	19	31	40	681.00114020440
HSK-A 63	60	27	21	33	48	681.00114020450

For milling cutters with longitudinal or tenon drive DIN 138

Rev. 12-1101 Page 2 of 2
Uncontrolled Document




Taper (D)	Length (L)	h6 (D1)	L1	L2	D2	Part Number
HSK-A 63	60	32	24	38	58	681.00114020460
HSK-A 63	70	40	27	41	70	681.00114020470
HSK-A 100	60	16	17	27	32	681.00114020630
HSK-A 100	60	22	19	31	40	681.00114020640
HSK-A 100	60	27	21	33	48	681.00114020650
HSK-A 100	60	32	24	38	58	681.00114020660
HSK-A 100	70	40	27	41	70	681.00114020670
HSK-A 100	80	50	30	46	90	681.00114020680

Available for HSK-A 32, 40, 50, 63, 80, 100

TAC Rockford Product Line

Machine Tool Gauges, Tool Changer Alignment, Runout Test Arbors, Workholding Systems, Tool Holders, Adapters and Extensions, Tool Holder Blanks, Machine Tool Accessories, Coolant Tubes and Gauges, Heat Shrink Systems, Rapid Prototyping


Tool Holders



Gauges



Accessories



Rapid Prototyping

