

Product Information

- Balancing quality: G6.3 / 15,000 rev./ min.
- Robust, radially operated length setting.
- Clamping- dia. for shank tolerance h6.
- To DIN 69 882-7

Scope of Delivery

- Includes clamping key.
- Includes hexagon key inserts for radial length setting.
- Order coolant delivery set separately.

Taper (d3)	Length (l1)	Ø h6 (d1)	Part Number
HSK-A 50	80	6	683.4296.006.050
HSK-A 63	80	6	683.4296.006.063
HSK-A 80	85	6	683.4296.006.080
HSK-A 100	85	6	683.4296.006.100
HSK-A 50	80	8	683.4296.008.050
HSK-A 63	80	8	683.4296.008.063
HSK-A 80	85	8	683.4296.008.080
HSK-A 100	85	8	683.4296.008.100
HSK-A 50	85	10	683.4296.010.050
HSK-A 63	85	10	683.4296.010.063
HSK-A 80	90	10	683.4296.010.080
HSK-A 100	90	10	683.4296.010.100
HSK-A 50	90	12	683.4296.012.050
HSK-A 63	90	12	683.4296.012.063
HSK-A 80	95	12	683.4296.012.080




Taper (d3)	Length (l1)	Ø h6 (d1)	Part Number
HSK-A 100	95	12	683.4296.012.100
HSK-A 63	90	14	683.4296.014.063
HSK-A 80	95	14	683.4296.014.080
HSK-A 100	95	14	683.4296.014.100
HSK-A 63	95	16	683.4296.016.063
HSK-A 80	100	16	683.4296.016.080
HSK-A 100	100	16	683.4296.016.100
HSK-A 63	95	18	683.4296.018.063
HSK-A 80	100	18	683.4296.018.080
HSK-A 100	100	18	683.4296.018.100
HSK-A 63	100	20	683.4296.020.063
HSK-A 80	105	20	683.4296.020.080
HSK-A 100	105	20	683.4296.020.100
HSK-A 63	120	25	683.4296.025.063
HSK-A 80	115	25	683.4296.025.080
HSK-A 100	115	25	683.4296.025.100
HSK-A 63	125	32	683.4296.032.063
HSK-A 80	125	32	683.4296.032.080
HSK-A 100	120	32	683.4296.032.100

Available for HSK-A 50, 63, 80, 100

TAC Rockford Product Line

Machine Tool Gauges, Tool Changer Alignment, Runout Test Arbors, Workholding Systems, Tool Holders, Adapters and Extensions, Tool Holder Blanks, Machine Tool Accessories, Coolant Tubes and Gauges, Heat Shrink Systems, Rapid Prototyping


Tool Holders



Gauges



Accessories



Rapid Prototyping

